


Pico Switch RED

Battery Backer/redundancy + Magnetic Switch



Battery/BEC inputs. IN1/IN2

Perfect for F5J

Output to your RC system - RX/Servos.



Sensor location "Sense"

Status LED

Installation & Use: -

"3 Second" Version - When the switch is plugged into the power supply for the first time the output will turn on and the LED will flash. Securely mount the switch as close to the fuselage or wing surface as possible. To locate the sensor simply sweep over the predicted sensor location, when the switch senses the magnet the LED will go solid (**ON**) indicating the perfect position. Use a marker pen and mark where the sensor is located and use a piece of double-sided tape and/or a piece of sponge to hold the switch in place. To turn the switch off, place the supplied magnet over the sensor and the **LED** will go solid (**ON**) then count for **3 seconds** or more without interruption the output will then turn **OFF**, the **LED** will flash to confirm and continue to flash until the magnet is moved away.

The "Swipe" version - Simply swipe the magnet over the sensor (slowly) to turn the output ON/OFF. Please allow 1.5 seconds between turning the switch OFF and then ON again.

Tips: -

3 Second Sample: To turn the switch OFF count **1, 1000, 2, 1000, 3, 1000.**

To turn the magnetic switch ON just swipe the magnet over the sensor.

Please ensure a full range check of the model is undertaken prior to use.

Warning!! -

Reversing the polarity of the supply **WILL** harm the switch. Please don't remove the protective heat shrink covering, doing so will void any warranty.

Ratings	
Supply Voltage	4V – 9V- 2s Li-po, 2 Life
Continuous Operating current	22AWG ~ 7A 20AWG + ~20A
Peak Output current	~ 14A (Max for seconds) ~ 50A MAX peak
Standby Current (Off State)	~ 4µA
Operating temperature range	-40°C +80°C
Dimensions ~	27.7mm x 14.06mm x 5.8mm (1.051" x 0.553" x 0.228")
Total cable length (Each)	Varies
Weight Including all cables	- Varies

Features: -

- Our intelligent Magnetic Switch knows what **ON/OFF** state it's in, If the battery is disconnected with the switch in its off state, it will remember this for Seconds. If the battery is disconnected when turned **ON**, the switch will be default **ON** when reconnected.
- **Battery Backer** - both In1 & In2 can be a battery or BEC/UBEC. Both supplies' may be used simultaneously if the voltages are the same, if a battery fails or goes under voltage the switch will disconnect that battery from the circuit, if it recovers, the switch will re-engage it.
- Our switches have an interactive feature - The LED flashes under normal use, when the magnet is placed over the active area, the LED goes solid "ON" as the magnet is sensed, as soon as the timer has counted 3 seconds the LED goes "OFF" and gives a confirmation FLASH until the magnet is moved away.
- **Swipe version** - The Blue LED is on constant until turned OFF.
- Our magnetic switch utilizes a Hall Effect Sensor (no mechanical switching parts). Careful firmware design ensures that stray magnetic fields cannot toggle the switch incorrectly; we guarantee 99.9% operating under normal conditions.
- Positively switched – Ideal for electric models, esc safe, there's no need for an opto isolator.
- Safe and reliable: - **Default ON** – if the battery is disconnected (whilst in its **ON State**) and then reconnected the output will turn **ON** 99.9% of the time. I.e. brownout due to bad battery connection. The magnetic switch is programmed to sample the magnet over the sensor for a set period without interruption and only then will it turn the output OFF. Extremely resilient to magnetic interference due to the switches microcontroller that is programmed with an algorithm.

Note: This is not a voltage regulator it is only used as a switch thus switching the battery voltage to your receiver, servos etc. It is not recommended to install the switch near electric motors and servos or anything that can create a magnetic field (110 Gauss operates the switch). We will not be held liable for any accidents caused by improper use or incorrect connection of our devices. It is up to the operator to maintain his/her Health & Safety. We will not be responsible for damage caused by external influences. Use at your own risk.

Our data sheet can be changed at any time without prior notice.

Pico Switch Red - Hall Magnetic Switch	
All content © Copyright practicalrc.com	14012019

<http://www.practicalrc.com>

